

Product name	Stopseal® Putty
Product Code	C1000
Revision Date	25/05/09
Revision number	01
Ref	PDS PUTTY



INTRODUCTION

Firestopit Stopseal® Putty is a solvent free putty for fire barriers up to 4 hours. It is designed as a joint filler and sealer for use in penetration seals.

Stopseal® Putty is designed to remain flexible allowing for thermal and mechanical movement of services around complex and irregular shapes through walls or floors.

The advantages of Stopseal® Putty are as follows:

- Non-setting, intumescent compound.
- Free of halogens, asbestos, fibres and silica.
- Not effected by fungal attack or moisture.
- Long life and easy to use.



SPECIFICATION

Colour	White
Density	1.55 g/cm ³
pH Value	8.2
Shelf Life	5 years
Odour	Wet: Negligible Dry: None
Toxicity	Non-toxic
Solids	82%



INSTALLATION

Installation details and technical support are available from Firestopit technical department or on the internet at www.firestopit.com

- Clean all loose material and foreign matter from the opening.
- Free from dust and oil.
- Ensure that services are in place.
- Pack the FSI Stopseal® Putty around the service into the opening to the required depth.
- Joint should be dry to the touch within 2 hours.
- Equipment can be cleaned with water.
- Inspect the workmanship of the seal and maintain a record.

For further information see Installation Manual.



COMPLIANCE

Stopseal® Putty is are manufactured in the EU, meeting the highest quality standard in compliance to BS EN ISO 9001:2008. For fire test certification contact Firestopit technical department.

CERTIFIRE No. CF515



STORAGE AND DISPOSAL

Stopseal® Putty should be stored between 5°C and 30°C. It should be protected from freezing. Shelf life is 5 years. Waste product is considered to be non-hazardous.